
# Maya slim


CEILING LIGHT

SA5(3/5)1XX-XX

IP20

STRIP LED 150°




## Maya slim installation manual

Read carefully and keep for future reference.

## Testing and Certification

All our products are Made in Italy, Certified and individually tested according to the EN60598-2 electrical safety directives:

- Dielectric Strength Measurement
- Earth Continuity Resistance Measurement
- Power Consumption Measurement
- Residual Voltage Measurement

## Warnings

Our products are fitted with light sources that can be replaced by specialized users.
Energy classes are indicated on the relevant technical data sheets at www.amarcords.com

Please ensure that the appliance is not subjected to mechanical loads.

Handle the appliance with care. The device can be damaged by impacts, knocks, or falls, even from a small height.

Before use, check that the device shows no visible external damage. Do not use the appliance if it is damaged.

Do not open the housing, as this could cause an electric shock.

Do not attempt to disassemble, repair, or otherwise modify the appliance.

LED light sources may only be replaced by specialized personnel.

Repairs and installations must be carried out exclusively by a qualified technician. Never attempt to repair the appliance yourself. Improper repairs can pose significant risks to the user and will invalidate any warranty claim.

The warranty is immediately void in the event of damage resulting from failure to comply with these instructions. The manufacturer accepts no liability for damage resulting from failure to follow these instructions, improper use, or use not in accordance with the conditions of this user manual.

Do not allow children to clean or repair the appliance without supervision.

To avoid damage, never immerse the unit in water or any other liquid.

Warning! Do not look directly at the lit LEDs of the product for long periods of time. LED sources can cause eye damage or irritation. Do not view the light source directly using an optical instrument that concentrates the light beams.



Sede legale: Via Piero della Francesca, 35 - 20154 Milano – Logistica e Uffici: Via G.Falcone, 7 - 20024 Garbagnate Milanese (MI) P.Iva 09021550968
Tel. +39 02 97132845 Sdi: SUBM70N

STRIP LED 150°

## Maya 30 slim

SA531XX-XX

| | |
|---|---|
| Power | 28W |
| Luminous fl. | 2700K-3460lm<br>3000K-3760lm<br>4000K-4014lm |
| Voltage | 230 VAC |
| Lifetime | 50.000 h |
| Dimming steps | 3 STEP |
| Class | Class II |
| Ambient t. | TA25°C |
| CRI | ≥90 |
| Energy class | |

## Maya 50 slim

SA551XX-XX

| | |
|---|---|
| Power | 45W |
| Luminous fl. | 2700K-5824lm<br>3000K-6160lm<br>4000K-6468lm |
| Voltage | 230 VAC |
| Lifetime | 50.000 h |
| Dimming steps | 3 STEP |
| Class | Class II |
| Ambient t. | TA25°C |
| CRI | ≥90 |
| Energy class | |


The product is supplied with Amarcords LED strps with energy efficiency class F/G.

### 01 Ensure that the main power is disconnected




Before performing any installation or maintenance work on the product, ensure that the main power is disconnected.

### 02 Separating the flat bracket



Separate the flat bracket from the lamp body.

### 03 Ceiling fixing and safety anchoring




Firmly fix the flat bracket to the ceiling using the appropriate wall plugs. During this operation, secure the safety cord to the ceiling, so as to anchor the lamp body.



Sede legale: Via Piero della Francesca, 35 - 20154 Milano – Logistica e Uffici: Via G.Falcone, 7 - 20024 Garbagnate Milanese (MI) P.Iva 09021550968
Tel. +39 02 97132845 Sdi: SUBM70N


## 04 → Electrical connection



Connect the supplied 3-way terminal block to the mains cables, making sure there is no mains voltage present for the entire duration of the installation. Make the connections according to the following colour code:

- Brown or Black → with Brown/Black (live)
- Blue → with Blue (neutral)
- Yellow/Green → with Yellow/Green (earth)


## 05 → Magnetic closure of the product



Bring the lamp body close to the flat bracket fixed to the ceiling until it is held firmly in place by the magnets.
Make sure the magnets are correctly aligned and provide a firm hold.

## 06 → Final position

The product will then be installed in its final position.





Sede legale: Via Piero della Francesca, 35 - 20154 Milano – Logistica e Uffici: Via G.Falcone, 7 - 20024 Garbagnate Milanese (MI) P.Iva 09021550968
Tel. +39 02 97132845 Sdi: SUBM70N